

VX-450 SERIES

BUILT TO LAST

-  GOODBYE CROSSTALK
-  BROADEN YOUR REACH
-  COME IN LOUD AND CLEAR
-  KEEP YOUR TEAM SAFE
-  POWER THROUGH THE SHIFT

PORTABLE ANALOGUE RADIOS

For robust, dedicated push-to-talk communication, look to the VX-450 Series.

Choose from three analogue portable radios: the VX-451 (without display) and the VX-454/VX-459 (with display). Water submersible and with a rugged construction, it's built for use in harsh conditions. With enhanced interoperability, the VX-450 series offers comprehensive signalling options including: MDC1200®, DTMF, deeper and richer 2-tone options, as well as 5-tone capabilities. Available with a range of flexible energy solutions and accessories, you'll have all you need to provide your team with the perfect communication solution.



GENERAL FEATURES

- Channel Capacity:
 - 32 Channels/ 1 Group (VX-451)
 - 512 Channels/ 32 Groups (VX-454, VX-459)
- Programmable Buttons:
 - 3 Programmable Buttons (VX-451)
 - 7 Programmable Buttons (VX-454)
 - 9 Programmable Buttons (VX-459)
- Display:
 - No Display (VX-451)
 - 8-Character Alphanumeric Display (VX-454/459)
- Safety Features:
 - Lone Worker Alert
 - Emergency Alert
- Solid Build for Extreme Environments (IP57)
- Voice Inversion Encryption
- Manual On/Off Encryption Activation
- Large Group Communication Made Easy to Manage
- RX/TX Battery Power Save
- Comander
- Clear Voice
- Whisper

- Minimum Volume Control
- Manual Squelch Adjustment
- Busy Channel Lock Out (BCLO)
- Busy Tone Lock Out (BTLO)
- Time Out Timer (TOT)
- Programmable LED Colour Alert
- Scan Features:
 - Priority
 - Dual Watch
 - Follow-Me
 - Talk Around
- Radio-to-Radio Cloning

SIGNALLING FEATURES

- CTCS/DCS Encode/Decode
- MDC-1200® Encode/Decode
- 2-Tone, 5-Tone Encode/Decode
- DTMF ANI
- DTMF Paging
- DTMF Speed Dial
- Stun/Kill/Revive (5-Tone)



GENERAL SPECIFICATIONS

	VHF	UHF
Frequency Range	134 - 174 MHz	400 - 470 MHz
Number of Channels and Groups	512/32 Groups (VX-459, VX-454) 32/2 Groups (VX-451)	
Power Supply Voltage	7.4 V DC (Nominal)	
Channel Spacing	12.5/20/25 kHz	
PLL Steps	1.25/2.5/5/6.25 kHz	5/6.25 kHz
Battery Life (5-5-90 Duty) 2300 mAh FNB-V134LI-UNI 1380 mAh FNB-V133LI-UNI	18.5 hours (W/Saver)/16 Hours 11 hours (W/Saver)/10 Hours	18 hours (W/Saver)/15.5 Hours 11 hours (W/Saver)/10 Hours
IP Rating	IP57	
Operating Temperature Range	-30°C to +60°C (-22°F to +140°F)	
Frequency Stability	±2.5 ppm	
RF Input-Output Impedance	SMA 50 Ohm	
Dimension (H x W x D) VX-451 Model	109 x 58 x 43 mm (4.3 x 2.3 x 1.7 Inches) FNB-V134LI-UNI 109 x 58 x 35 mm (4.3 x 2.3 x 1.4 Inches) FNB-V133LI-UNI	
Weight (Approx.) with Antenna, Belt Clip VX-451; VX-454/459	330 g; 356 g (11.6 oz; 12.6 oz) FNB-V134LI-UNI 281 g; 307 g (9.9 oz; 10.8 oz) FNB-V133LI-UNI	

RECEIVER SPECIFICATIONS

measured by EN 300 086

Sensitivity 20dB SINAD	-2 dB μ V Typical
Adjacent Channel Selectivity	70 dB/65 dB
Hum and Noise	45 dB/40 dB
Intermodulation	70 dB/65 dB
Spurious and Image Rejection	70 dB
Audio Output	700 mW (Internal @ 16 Ohms, 5% THD) 500 mW (External @ 4 Ohms, 5% THD)

TRANSMITTER SPECIFICATIONS

measured by EN 300 086

Output Power	5/2.5/1/0.25 Watt (Selectable by Channel)
Modulation	16K0F3E / 14K0F3E / 11K0F3E
Maximum Deviation	± 5.0 kHz / ± 4 kHz / ± 2.5 kHz
Conducted Spurious Emissions	70 dB Below Carrier
FM Hum and Noise	45 dB/40 dB
Audio Distortion	< 3 % @ 1 kHz

APPLICABLE MIL-STD

Standard	Methods/Procedures				
	MIL 810C	MIL 810D	MIL 810E	MIL 810F	MIL 810G
Low Pressure	500.1 proc 1	500.2 proc 1/2	500.3 proc 1/2	500.4 proc 1/2	500.5 proc 1/2
High Temperature	501.1 proc 1/2	501.2 proc 1/2	501.3 proc 1/2	501.4 proc 1/2	501.5 proc 1/2
Low Temperature	502.1 proc 1	502.2 proc 1/2	502.3 proc 1/2	502.4 proc 1/2	502.5 proc 1/2
Temperature Shock	503.1 proc 1	503.2 proc 1	503.3 proc 1	503.4 proc 1	-
Solar Radiation	505.1 proc 1	505.2 proc 2/Cat A1	505.3 proc 2/Cat A1	505.4 proc 1/2/Cat A1	-
Rain	506.1 proc 1/2	506.2 proc 1/2	506.3 proc 1/2	506.4 proc 1/3	506.5 proc 1/3
Humidity	507.1 proc 1/2	507.2 proc 2/3	507.3 proc 2/3	507.4 proc 3	507.5 proc 1/3
Salt Fog	509.1 proc 1	509.2 proc 1	509.3 proc 1	509.4 proc 1	509.5 proc 1
Dust	510.1 proc 1	510.2 proc 1	510.3 proc 1	510.4 proc 1/3	510.5 proc 1
Vibration	514.2 proc 8/10	514.3 Cat 10	514.4 Cat 10	514.5 Cat 20/24	514.6 Cat 20/24
Shock	516.2 proc 1/3/5	516.3 proc 1/4	516.4 proc 1/4	516.5 proc 1/4	516.6 proc 1/4



ACCESSORIES

Antennas

- ATU-16B: 400-420 MHz 157 mm (6.8")
- ATU-16BS: 400-430 MHz 87 mm (3.43")
- ATU-16C: 420-450 MHz 151 mm (5.94")
- ATU-16D: 450-470 MHz 138 mm (5.43")
- ATU-16DS: 450-490 MHz 87 mm (3.43")
- ATV-16A: 136-150 MHz 137 mm (5.39")
- ATV-16B: 150-163 MHz 137 mm (5.39")
- ATV-16C: 162-174 MHz 137 mm (5.39")
- ATV-16XL: Untuned 192 mm (7.55") VHF

Battery

- FNB-V133LI-UNI: 1380 mAh Li-Ion Battery
- FNB-V134LI-UNI: 2300 mAh Li-Ion Battery
- FNB-V136-UNI: 1200 mAh Ni-MH

Carry Solutions

- LCC-133LN: Belt Loop Case (FNB-V133LI-UNI) No Display
- LCC-134LN: Belt Loop Case (FNB-V134LI-UNI) No Display
- LCC-133SN: Swivel Belt Clip Case (FNB-V133LI-UNI) No Display
- LCC-134SN: Swivel Belt Clip Case (FNB-V134LI-UNI) No Display
- LCC-133LD: Belt Loop Case (FNB-V133LI-UNI) Display
- LCC-134LD: Belt Loop Case (FNB-V134LI-UNI) Display
- LCC-133SD: Swivel Belt Clip Case (FNB-V133LI-UNI) Display
- LCC-134SD: Swivel Belt Clip Case (FNB-V134LI-UNI) Display
- CLIP-20: Belt Clip

Chargers

- PA-55C: AC Power Adapter for CD-58 (EU Plug)
- PA-55U: AC Power Adapter for CD-58 (UK Plug)
- CD-58: Single Unit Charger
- VAC-6058: Multi Unit Charger for UNI Batteries
- VCM-5: Vehicle Charger Mounting Adapter

Audio Accessories

- MH-100: 3.5 mm Earpiece for RSM Audio Jack
- MH-101A4B: 1 Wire Surveillance Kit
- MH-102A4B: 2 Wire Surveillance Kit
- VH-150A: Lightweight Behind-the-Head VOX Headset, IS
- VH-150B: Lightweight Over-the-Head VOX Headset, IS
- MH-360S: Compact Speaker Microphone
- MH-37A4B: Earpiece Microphone
- MH-450S: Speaker Microphone
- MH-45B4B: Noise Cancelling Speaker Microphone

Option Boards

- DVS-9: Man Down Alert with Digital Voice Storage



VX-451

VX-454

VX-459

Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, UK. www.motorolasolutions.com

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2017 Motorola Solutions, Inc. All rights reserved. 11-2017